


# HOW TO READ YOUR QUOTE

 <b>Pulley Quote</b> PPI-USA BOX 287, 300 S.E. 14TH ST PELLA, IOWA 50219 (641) 628-3115 FAX (641) 628-3658 WWW.PPI-GLOBAL.COM	Prepared For	<b>Quote#</b>			
	Phone: Fax: ATTN: Cust#:	Page: 1  Quote Date: Revised: Good Until: Est Ship:			
Project: Inquiry: Terms:					
<b>Count On Us To Meet Your Conveyor Component Needs</b> Outside Rep: _____ Inside Rep: _____					
Cnv.ID / Loc.	Qty	Description	Weight (LBS)	Price Each	Ext. Total
	1	14X32 CF PXT30 PRO DUTY DRUM	181		
	1	PXT30B 2 15/16 XT BUSH W/BOLT			
	1	.3750 HBG SBR 60 L	23		
	1	2.9375X51.0000 SHAFT 3KS	98		
		2 15/16 C1045 T&P			
	2	2.9375 TYPE E PB 2B PPI	29		
		**** 001 **** TOTAL ASSEMBLY	331		
	1	14X32 CF WING PULLEY W/PXT30	170		
	1	PXT30B 2 15/16 XT BUSH W/BOLT			
	1	2.9375X51.0000 SHAFT CM	98		
		2 15/16 C1045 T&P			
	2	2.9375 TYPE E PB 2B PPI	29		
		**** 002 **** TOTAL ASSEMBLY	297		
	1	14X32 RC HB WING W/PXT30	211		
	1	PXT30B 2 15/16 XT BUSH W/BOLT			
	1	2.9375X51.0000 SHAFT CM	91		
		2 TDT 2.4375			
		2 15/16 C1045 T&P			
	2	2.4375 TYPE E PB 2B PPI	20		
		**** 003 **** TOTAL ASSEMBLY	322		
			<b>Total Est. Weight(LBS)</b>	<b>950</b>	<b>TOTAL (USD)</b>
					\$

PULLEY	BUSHING/BORE STYLE	SHAFTING	BEARING
DIAMETER X FACE WIDTH	FB= FIXED BORE	DIAMETER X LENGTH	SHAFT DIAMETER THROUGH BEARING
PULLEY CROWN	SSP = STATIC SHAFT	CM = CENTER MOUNT	BEARING TYPE
HUB SIZE	EZ= STUB SHAFT	NUMBER OF KEYS (KS=KEYWAY(S))	BEARING STYLE
PULLEY TYPE	RB = KEYLESS LOCKING	TDT = TURNDOWN TO DIAMETER	BEARING MANUFACTURER
CF = CROWNED FACE	WELDIN = SHAFT WELDED	D&T = Drill & Tap	BC = BEARING CENTERS MATERIAL GRADE
FF = FLAT FACE	BORE SIZE (SHAFT DIAMETER)		
RC = RADIUS CROWN	BUSHING STYLE		
	<b>LAGGING</b>		
	THICKNESS		
	GROOVING		
	MATERIAL		
	DUROMETER		

# HOW TO READ YOUR QUOTE

PULLEY		SHAFTING		LAGGING		SPECIAL	
FF	FLAT FACE	HR	HOT ROLL	HBG	HERRINGBONE GROOVE	MTO	MACHINE TO
CF	CROWN FACE	CD	COLD DRAWN	PL	PLAIN	SB	STATIC BALANCE
EC	EDGE CROWN	T&P	TURNED & POLISHED	DIA	DIAMOND GROOVE	SI	SPECIAL INSET
TC	TRAPAZOIDAL CROWN	TG&P	TURNED, GROUND & POLISHED	CHE	CHEVRON GROOVE	CSP	CUSTOMER SUPPLIED PRODUCT
RC	RADIUS CROWN	CF	COLD FINISHED	VRT	VULCANIZED ROUGH TOP	CSC	CUSTOMER SUPPLIED COMPONENT
MCF	MACHINE CROWN	D&T	DRILL & TAP	NIT	NITRILE	TSR	THERMAL STRESS RELIEVE
MFF	MACHINE FLAT	KS	KEYWAY(S)	VEC	PPI VULCANIZED CERAMIC	UT	ULTRASONIC TEST
MEC	MACHINE EDGE CROWN	KFL	SHAFT KEY FULL LENGTH	COMBI GRIP	RICHWOOD 475 PIW CERAMIC LAGGING PAD	MT	MAGNETIC PARTICLE TEST
MTC	MACHINE TRAP CROWN			COMBI LAG	RICHWOOD 1,000+ PIW CERAMIC LAGGING PAD		
PRO	PROFILE DISC			FLEX LAG.	FLEXCO DIAMOND CERAMIC LAGGING		
INT	INTEGRAL HUB			FAS-LAG	REPLACABLE WING PULLEY LAGGING		
ST	SENSOR TARGETS			CRAFT-LAG	REPLACABLE PULLEY LAGGING PADS		
SEP	STANDARD EPOXY			NEO	NEOPRENE RUBBER		
PEP	PREMIUM EPOXY			URE	URETHANE OR POLYURETHANE		
CEP	CANADA EPOXY PAINT			AR	ABRASION RESISTANT		
UH	UNIT HANDLING			DURO	DUROMETER (HARDNESS OF THE RUBBER)		
MD	MINE DUTY WING			F.O.D	FINAL OUTSIDE DIAMETER		
HB	HERRINGBONE WING						
QM	QUARRY MAX WING						
SPI	SPIRAL						
MDSPI	SPIRAL PLUS WING (MINE DUTY)						
SD	SINGLE DISC ELEVATOR						
CHB	CEMA JERRINGBONE WING						
TURB	TURBINE						
S4	304 STAINLESS STEEL						
S6	306 STAINNLESS STEEL						
WINGS & CAGE DESIGNS							
AR	AR BAR						



300 SE 14TH STREET PELLA, IA 50219 | 800.247.1228 | WWW.PPI-GLOBAL.COM

Product shown are for illustrative purposes only and may display optional accessories or components. Please contact your sales representative for more information on product specifications. PPI respectively reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice obligation. PPI and its respective logos are trademarks of Precision, Inc. in the US and/or other countries.