

HOW TO READ YOUR QUOTE



Pulley Quote

PPI-SS
1615 E. POPLAR STREET
ALGONA, IA 50511
(515) 295-2435
FAX (515) 295-7942
WWW.PPI-GLOBAL.COM

Prepared For

Quote# 000000

Page: 1

Phone:
Fax:
ATTN:
Cust#: 00000000

Quote Date: 4/30/19
Revised: 0/00/00
Good Until: 6/14/19
Est Ship:

Project:
Inquiry:
Terms:

Count On Us To Meet Your Conveyor Component Needs
Outside Rep:

Inside Rep:

Cnv.ID / Loc.	Qty	Description	Weight (LBS)	Price Each	Ext. Total
	1	1.2200X38.0000 SHAFT 1KS 1 TDT 0.6300 1 TDT 0.9830 1 TDT 0.9830 1 1/4 304SS T5 TIMING ROLL 20 TOOTH RELIEF GROOVES **** 001 **** TOTAL ASSEMBLY	12		
	1	06.29X36.00 FF ACETAL BORE = 1.4375 DELRIN/SS SANITARY PULLEY 8050 GROOVES	60		
	1	1.4375X52.0000 SHAFT 1 5/8 304SS **** 002 **** TOTAL ASSEMBLY	24		84
	1	06.40X29.46 WELDIN 304SS TUBE :FF KNURLED LESS BUSHINGS **** 003 **** TOTAL ASSEMBLY	101		101
	1	06.00X20.00 TC PXT20S4 304SS N TUBE PXT20B 1 15/16 304SS W/BOLT	25		
	1	.2500 :60 DURO WHITE FDA XNBR	0		
	1	1.9375X32.0000 SHAFT 3KS 1 15/16 303SS BSQ **** 004 **** TOTAL ASSEMBLY	27		52

PULLEY	BUSHINGS	HAFTING
DIAMETER X FACE WIDTH	WELDIN = SHAFT WELDED (NO BUSHING)	DIAMETER X LENGTH
PULLEY CROWN	BORE SIZE (SHAFT DIAMETER)	CM = CENTER MOUNT
HUB SIZE	BUSHING STYLE	NUMBER OF KEYS
PULLEY TYPE	LAGGING	KS = KEYWAY(S)
CF = CROWNED FACE		TDT = TURNDOWN TO DIAMETER
FF = FLAT FACE	THICKNESS	D&T = Drill & Tap
RC = RADIUS CROWN	GROOVING	MATERIAL GRADE
	MATERIAL	
	DUROMETER	

HOW TO READ YOUR QUOTE

PULLEY		SHAFTING		LAGGINGS		PECIAL	
FF	FLAT FACE	HR	HOT ROLL	HBG	HERRINGBONE GROOVE	SB	STATIC BALANCE
CF	CROWN FACE	CD	COLD DRAWN	PL	PLAIN	IH	INTEGRAL HUB
EC	EDGE CROWN	T&P	TURNED & POLISHED	DIA	DIAMOND GROOVE	SI	SPECIAL INSET
TC	TRAPAZOIDAL CROWN	TG&P	TURNED, GROUND & POLISHED	CON	CONCENTRIC/ CIRCUMFERENTIAL GROOVE	CSP	CUSTOMER SUPPLIED PRODUCT
RC	RADIUS CROWN	CF	COLD FINISHED	PAR	PARALLEL GROOVE	CSC	CUSTOMER SUPPLIED COMPONENT
MCF	MACHINE CROWN	KFL	SHAFT KEY FULL LENGTH	CHE	CHEVRON GROOVE		
MFF	MACHINE FLAT	BSQ	BEARING SHAFT QUALITY	SRT	SPIRAL ROUGH TOP		
MFT	MACHINED FACE TUBE			VRT	VULCANIZED ROUGH TOP		
S4	304 STAINLESS STEEL			NIT	NITRILE		
S6	316 STAINLESS STEEL			NEO	NEOPRENE RUBBER		
MTC	MACHINE TRAP CROW N			URE	URETHANE OR POLYURETHANE		
WINGS & CAGE DESIGNS				DURO	DUROMETER (HARDNESS OF THE RUBBER)		
				XNBR	CARBOXYLATED WHITE NITRILE - FDA		
				F.O.D.	FINAL OUTSIDE DIAMETER		
SANITARY PULLEY				MTO	MACHINE TO		
DELTRIN	BODY + STAINLESS SHAFT			GTO	GRIND TO		



300 SE 14TH STREET | PELLA, IOWA 50219 | 800.247.1228 | WWW.PPI-GLOBAL.COM

Product shown are for illustrative purposes only and may display optional accessories or components. Please contact your sales representative for more information on product specifications. PPI respectively reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice obligation. PPI and its respective logos are trademarks of Precision, Inc. in the US and or other countries.