



Apron feeders are a common method for controlled feeding of material. Often, they are located below a primary jaw or gyratory crusher, stockpile or rail unloading station. Dozer chain is typically used for its strength and reliability. Sprockets utilized by PPI work with standard chain sizes including: D2, D4, D6, D7, D9, D10, and D11.

PPI produces the drive and idler shaft assemblies (not the apron feeder) for many of the largest OEM's supplying apron feeders to the market. PPI apron feeder shafts are currently used in copper, gold, cement and other types of mining operations. PPI has extensive engineering expertise and experience ensuring these components provide ultimate reliability.

FEATURES AND BENEFITS

- Designed by PPI engineers to meet customer needs
- Manufactured for long wear and maintenance-free service

OPTIONS

- Keyless fitting and machined hub to bolted sprocket
- Cone integrated flange coupling to bolted sprocket
- Splined flange coupling to splined and bolt sprockets

WWW.PPI-GLOBAL.COM | SALES@PPI-GLOBAL.COM

Product shown are for illustrative purposes only and may display optional accessories or components. Please contact your sales representative for more information on product specifications. PPI respectively reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice obligation. PPI and its respective logos are trademarks of Precision, Inc. in the US and or other countries.
PPI 108-02 Copyright ©2021 Precision Pulley & Idler, all rights reserved.