



PPI catenary structure incorporates a user friendly design that allows easy assembly and tear down that lets the operator reconfigure their conveyor as the mining process dictates. Floor stands equipped with chain-slot brackets allow roof or floor mount configurations based on specific terrain at the mine. Available in CEMA C, D, and E for 24" - 60" belt widths. For wider belts please call for application assistance.

## FEATURES AND BENEFITS

- Integrated roof hangers allow for chain mount when the surface below does not permit
- Quick locking connection makes assembly and disassembly efficient
- Adjustable legs enable the structure to be set up on uneven surfaces
- Oversized handles on both the troughing idlers and returns make handling effortless, even with gloves
- Gusseted frames ensure the frames will stand the test of time, even after many moves
- Heavy duty galvanized stringers
- Stand alone structure utilizing PPI's trusted roll design
- Rolls built with PPI's LXT seal system promote long roll life
- Unparalleled customer support that comes along with PPI
- Quick lead times on product, when down time is not an option
- Service centers strategically located to better serve customers
- PPI's high quality conveyor components at a competitive price
- Standard warranty on rolls and framework—with extended warranty available for some applications



USA | CANADA | CHILE

[www.ppi-global.com](http://www.ppi-global.com) | [sales@ppi-global.com](mailto:sales@ppi-global.com)

Product shown are for illustrative purposes only and may display optional accessories or components. Please contact your sales representative for more information on product specifications. PPI respectively reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice obligation. PPI and its respective logos are trademarks of Precision, Inc. in the US and or other countries.