


CATENARY IDLER STRUCTURE



PPI catenary structures incorporate a user friendly design allowing for ease of assembly and tear down while letting the operator reconfigure their conveyor as the mining process dictates. Floor stands equipped with chain-slot brackets allow roof or floor mount configurations based on specific terrain at the mine. Available in CEMA C, D, and E for 24" - 60" belt widths. For wider belts please contact your sales representative for assistance.

FEATURES AND BENEFITS

- Integrated roof hangers allow for chain mount when the surface below does not permit
- Quick locking connection makes assembly and disassembly efficient
- Adjustable legs enable the structure to be set up on uneven surfaces
- Oversized handles on both the troughing idlers and returns make handling effortless, even with gloves
- Gusseted frames ensure the frames will stand the test of time, even after many moves
- Heavy duty galvanized stringers
- Stand alone structure utilizing PPI's trusted roll design
- Rolls built with PPI's LXT seal system promote long roll life
- Unparalleled customer support that comes along with PPI
- Standard warranty on rolls and framework—with extended warranty available for some applications

WWW.PPI-GLOBAL.COM | SALES@PPI-GLOBAL.COM

Product shown are for illustrative purposes only and may display optional accessories or components. Please contact your sales representative for more information on product specifications. PPI respectively reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice obligation.

PPI and its respective logos are trademarks of Precision, Inc. in the US and or other countries.

PPI 040-04

Copyright ©2021 Precision Pulley & Idler, all rights reserved.

06/21